## Water Quality Criteria

The Spokane River water quality classifications and dissolved oxygen criteria are:

Portion Of Study Area	Classification	Classification Dissolved Oxygen Criterion
Lake Spokane or Lake	Lake Class	No measurable decrease from natural conditions.
Spokane (from Lake Spokane		
Dam to Nine Mile Bridge)		2
Spokane River (from Nine Mile	Class A	Dissolved oxygen shall exceed 8.0 mg/L. If "natural
Bridge to the Idaho border)		conditions" are less than the criteria, the natural
		conditions shall constitute the water quality criteria.

In addition, the Spokane River has the following specific water quality criteria (Ch. 173-201A-

Special conditions: Spokane River from Lake Spokane Dam (RM 33.9) to Nine Mile Bridge (RM 58.0).

(a) The average euphotic zone concentration of total phosphorus (as P) shall not exceed 25 ug/L during the period of June 1 to October 31.







Figure C1. Model predicted dissolved oxygen profiles for Lake Spokane at model segments 188 for the CURRENT, NO-POINT, NO-SOURCE, PERMIT, and SOD scenarios on Julian days 181.25 (Jun 15), 258.25 (Sep 15), 273.25 (Oct 1).


TMDL Schedule w/ existing WO criteria	TMDL Approval F	Phase I - Interim Nutient Removal	Nutient Ren	noval	Phase 2		-Final TMDL Goal - Meet DO Criteria	- Meet D	O Criteri	a
	Maria System South							GIG Duy		ing iol
Point Sources	Planning for Max TP removal and reuse		Construction	MAX TP removal in-place	Meet natural t	Meet natural background conc or Imp Reuse - Lake Monitor - Complete UAA	or Imp Reuse	- Lake Mo	onitor - Com	plete UAA
es que estable estab estab estable estable estab estable estable estab estab estab estab estab estab estab est					9(54) (968) 2011 (276)			200 100 200	unius 184	ne in Lacis Vicili APS
Nonpoint Sources	Tributary TMDLs completed with Imp Plan	19.00	Begin Implement BMPs	BMPs	Complete imp		lement BMPs w/ monitoring and adaptive approach	ing and ad	aptive appr	oach .
に勝りばるはは	CONTRACTOR OF STREET	の は こことの ない	S. Sign	なはない。		THE RESIDENCE OF THE PERSON NAMED IN		The Personal Property lies		というない はないことのできる
Estimates of Ph	Estimates of Phosphorus Loading Reduction (2003 Pt Src flows)	g Reduction	(2003 Pt	Src flows)	Agrija Agraj Barija Barija	Tiple is Hry-typ Tables	1   5   G 2 6   2   19 11   2   18	drive drive	water euse fille i	agang Mangle Kang
Estimates of Ph	osphorus Loadin	g Reduction	(2003 Pt Src flov Max TP removal Load @ 50 ug/L- all to river	Src flows)  noval Load all to river		nnin 1694) 1886	7	oquee iduite	Logical Services	P Final gos
Estimates of Ph	osphorus Loading F  Existing Avg TP load  Summer 2003  #/day Flow MGD	g Reduction	(2003 Pt : Max TP ren @ 50 ug/L- #/day	103 Pt Src flows) Max TP removal Load @ 50 ug/L- all to river liday   Flow MGD		non North Same	5 gist 6 gist 3 gist	Film Carico Idente	Load at 7	oad at TP Final goa © 10 ugL to River day Flow MGI
Estimates of Ph	Existing Avg IP load Summer 2003 #/day Flow M 6.9 3.2	g Reduction	(2003 Pt : Max TP ren @ 50 ug/L. #/day 0.4	Src flows) hoval Load hoval Load all to river Flow MGD 3.2	1211 1711 1811 1811 1811 1811	1947 li 1934 ja 1932 ja	6 9 8 9 8 9 8 9 8 9 9 9 9 9 9 9 9 9 9 9	Genec draw	Load at 8 10 u	P Final goa gL to River Flow MGI
Estimates of Ph  Discharger CDA Hayden Post Falls Liberty Lake	Existing Avg TP load Summer 2003 #/day Flow M 6.9 3.2 seaonal land app 4.1 2.1 9.1 0.7	g Reduction	(2003 Pt Src fle  Max TP removal Lo @ 50 ug/L- all to ri #/day Flow 0.4 3. seaonal land app 0.4 2. 0.1 0.1	Src flows) noval Load noval Load all to river Flow MGD 3.2 and app 2.1 0.7			1 C 29	cynics drute turi til	Load at 1 @ 10 u #/day 0.1	IP Final gos gL to River Flow MGI 32 g P renoval
Estimates of Ph  Discharger CDA Hayden Post Falls Liberty Lake Kaiser IEP	osphorus Loading Resisting Avg TP load Summer 2003 ##day Flow Migd 6.9 3.2 seaonal land app 4.1 2.1 9.1 0.7 0.1 0.1 (Outlast 02+03 9.8 4.6"	g Reduction	(2003 Pt*  Max TP ren @ 50 ug/l.  #/day 0.4  Seaonal 0.4  0.1  0.1  0.1  1.1	Src flows) noval Load noval Load all to river Flow MGD 32 and app 2.1 0.7 16* 4.8	If effluent TP ma effluent TP loading as long as in-stre	P meets instreating can increating can increasing c	an conc. does not increase	cynce draw	Load at 1 @ 10 u #/day 0.1 0.0 0.1 0.0 1.3	TP Final goz gL to River Flow MG TP removal QP removal Q.7 16.0
Estimates of Ph  Discharger CDA Hayden Post Falls Liberty Lake Kaiser IEP Spokane City/Cnty	Sphorus Loading           Existing Avg TP load           Summer 2003           #/day         Flow M           6.9         3.2           seagnal land app         4.1           9.1         0.7           0.1         0.0 (Outfall           9.8         4.8*           151.0         36.5	g Reduction	(2003 Pt*)  Max TP ren @ 50 ug/l- #/day 0.4 5.0000101 0.4 0.1 3.2 1.1 14.5	Src flows) noval Load all to river Flow MGD 3.2 and app 2.1 0.7 16* 4.8 38.5	If efficient 7 efficient TP locals long as in	If effluent TP meets instream target conc ffluent TP loading can increase with effluent fit as long as in-stream conc. does not increase	m target conc. se with effluent ces not increas	cynce draw	Load at 1 @ 10 w #day 0.1 0.0 1.3 0.2	TP Final goz gL to River Flow MGI 3.2 QP remova 2.1 0.7 16.0
Estimates of Ph  Discharger CDA Hayden Post Falls Liberty Lake Kaiser EP Spokane City/Cnty Spokane CSO&Storm	OSPhorus Loadin  Existing Avg TP load  Summer 2003  #iday Flow! 6.9 33  seaonal land app 4.1 2.3 9.1 0.1 (Outland 9.8 4.8 151.0 36	g Reduction	(2003 Pt*)  Max IP ren @ 50 ug/l. #/day 0.4 5eaonal 0.1 0.1 0.1 14.5 CSO elim & S.	Src flows) noval Load all to river Flow MGD 3.2 and app 2.1 0.7 16* 4.8 38.5	If efficient? efficient TP log as long as it	P meets instread ding can incread conc. of	m target conc. se with effluent oes not increas	cance dana tari til		TP Final goz gL to River Flow Miga 3.2 gP remova 2.1 0.7 16.0 4.8 36.5
Estimates of Ph  Discharger CDA Hayden Post Falls Liberty Lake Kaiser IEP Spokane City/Cnty Spokane CSO&Storm Tot. PS Load***	OSPhorus Loadin  Existing Avg TP load  Summer 2003  #/day Flow I  6.9 3.3  seaconal land app 4.1 0.3  9.1 0.1 (Outla  9.8 4.8  151.0 36  14.2 36	g Reduction	(2003 Pt Src flow:  Max TP removal Load  @ 50 ug/L- all to river  #iday Flow MGD  0.4 3.2  seaonal land app  0.4 2.1 0.1 0.1 0.1 0.2 16* 1.1 4.8 14.5 36.5  CSO elim & SW mgmt plans	Src flows) noval Load all to river Flow MGD 3.2 and app 2.1 0.7 16* 4.8 36.5	if effluent? effluent TP lo as long as i	P meets instreading can increa	m larget conc. se with effluent ces not increas	cynce draw	Load at 1 @ 10 u #/day 0.1 0.1 0.1 0.0 1.3 0.2 2.9 2.9 Reduce / E	P Final goad Lto River Flow MGI 3.2 3.2 3.7 9.7 16.0 7.16.0 4.8 36.5 conc-based iii m CSO & S
Estimates of Ph  Discharger CDA Hayden Post Falls Liberty Lake Kaiser IEP Spokane City/Cnty Spokane CSO&Storm Tot. PS Load*** Tributary Load (Natural+NPS)	Sphorus Loading           Existing Avg TP load           Summer 2003           #iday         Flow MG           6.9         3.2           seaonal land app         2.1           9.1         0.7           0.1         0.7           0.1         0.7           151.0         36.5           14.2         150.8           150.8         YR 2001	g Reduction	(2003 Pt*)  Max TP ren @ 50 ug/L- #/day 0.4 0.4 0.1 3.2 1.1 14.5 CSO elim & S) 150.8	Src flows) novai Load all to river Flow MGD 3.2 and app 2.1 0.7 16° 4.8 38.5 V mgmt plans	If effluent TP ma effluent TP loading as long as in-stre		ets instream target conc can increase with effluent flow am conc. does not increase b loads needed to meet TMDL	Sologia de la composición del composición de la		Load at TP Final goal  @ 10 ugL to River  #iday Flow MGD  0.1 3.2  arry spring P removai?  0.1 2.1  0.0 16.0  2.2 4.8  2.9 36.5  aduce / Ellim CSO & SV  4.6 conc-based lim

"with estimated Pattenuation
Point Source compliance schedule implemented via common Administrative Order then rolled into all individual permits within 2 years
Figure 10. Summary - Spokane R. Proposed TMDL and Phosphorus Loading Reduction Strategy (9-20-04)




ipokane Natural round TP Load Jmi + LSR) 287.5 594.3 225.3 98.9 67 79.7


Figure 9. Estimate of 2003 effective summer (June – October) phosphorus loading to Lk Spokane using natural condition estimates from CE-Qual-W2 and attenuated point source loadings estimated from the P- attenuation model for a 1-in-10 low flow year.




## Lake Spokane Phosphorous Loads with Current WWTP Flows



## Lake Spokane Phosphorous Loads Plus 50 Microgram Phosphorous at Current WWTP Flows



## Lake Spokane Phosphorous Loads Plus 10 Microgram Phosphorous @ Current WWTP Flow



00

J-U-B ENGINEERS, Inc.
ENGINEERS - SURVEYORS - PLANNERS